## Belgotex

























## PALACE LUX

























Construction	Tufted Cut Pile Carpet
Yarn	100% New Zealand Wool
Yarn Specification	3-ply yarn, hank dyed
Width	4.0m
Standard Roll Length	30m
Yarn Weight	2000g/m² / 59oz/yd²
Total Weight	2930g/m²
Pile Height	8.6mm
Total Thickness	11.9mm
Machine Gauge	1/4"
Backing	Action Bac
Fire Test	ISO 9239-1
Insect Resistance	Treated against insect and moth infestation.
Thermal Conductivity	0.17 m <sup>2</sup> / K/W
Underfloor Heating	Suitable
Luxury Class	LC 5
Rating	Class 23 Domestic Heavy / Class 32 Commercial Medium
Warranties	15 Year Best Wool Warranty Including: Lifetime Manufacturing Defects Warranty 5 Year Insect Resistance Warranty
Environmental	GUT Certified, Low VOC, EN 14041
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed.

- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
   Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
   Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Must be laid in accordance with AS/NZ Installation Standards.