

Belgotex







OSLO



Backing

Fire Test





















Construction	Tufted Loop Pile Carpet
Yarn	100% Pure Wool
Yarn Specification	4-ply yarn, undyed
Width	4.0m & 5.0m
Standard Roll Length	30m
Yarn Weight	1300g/m² / 38.3oz/yd²
Total Weight	2350g/m²
Pile Height	5.9mm
Total Thickness	10.2mm
Machine Gauge	1/4"

Insect Resistance Treated against insect and moth infestation. 0.17 m² / K/W Thermal Conductivity

Underfloor Heating Suitable **Luxury Class** LC 4

Class 23 Domestic Heavy / Class 33 Commercial Heavy Rating

Jute

ISO 9239-1

Warranties 15 Year Best Wool Warranty Including:

Lifetime Manufacturing Defects Warranty

5 Year Insect Resistance Warranty

Environmental GUT Certified, Low VOC, EN 14041

Installation Please contact Gilt Edge Industries for all adhesive and installation instructions.

NB: If recommended adhesive is not used, claims will not be accepted.

All seams must be sealed.

Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or www.irvineflooring.co.nz
 Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
 Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
 Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.