



Construction	Inlaid Sheet Vinyl (Non Phthalate Construction)
Width	1.83m
Standard Roll Length	31.09lm / 56.9m ²
Pattern Repeat	Random Repeat, Reverse Sheet for Seaming
Total Weight	3010g/m ²
Wearlayer Thickness	1.39
Total Thickness	2.03mm
Surface Protection	Quantum Guard®
Slip Resistance	DS-R10 (DIN51130)
Fire Rating	EN ISO 9239-1:2010
Dynamic Coefficient of Friction	ASTM C1028 – Meets ADA Guidelines
Electrical Propensity	< 2kV (EN1815)
VOC Rating	SCS Certified – FloorScore Indoor Air Quality Passed and Listed – CHPS 01350 Indoor Air Quality
Underfloor Heating	Suitable up to 32°C
Static Load Limit	500psi
Chemical Resistance	Good
Rating	Extra Heavy Duty Commercial
Warranty	10 Year Commercial Warranty
Environmental	100% Recyclable NSF / ANSI-332 Gold Certification
Installation	Random Repeat, Reverse Sheet for Seaming Cove fillet is required on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls need to be reverse laid to allow for colour inequality.