



Colours shown may vary slightly from the actual product and should be used only as a guide.





LOTUS























Construction	Tufted Loop Pile Carpet
Yarn	100% New Zealand Wool
Yarn Specification	3-ply yarn, hank dyed
Width	4.0m
Standard Roll Length	30m
Yarn Weight	1500g/m² / 44.2oz/yd²
Total Weight	2537g/m ²

Pile Height	5.5mm
Total Thickness	9.0mm
Machine Gauge	5/32"
Backing	OEBac
Fire Test	ISN 9239

Insect Resistance	Treated against insect and moth infestation.

Thermal Conductivity	0.15 m ² / K/W
Underfloor Heating	Suitable
Luxury Class	LC 5

Rating	Class 23 Domestic Heavy / Class 33 Commercial Heavy

Marrantics	15 Vaar Dast Wool Warranty
Warranties	15 Year Best Wool Warranty

Including:

Lifetime Manufacturing Defects Warranty

5 Year Insect Resistance Warranty

Environmental GUT Certified, Low VOC, EN 14041

Installation Please contact Gilt Edge Industries for all adhesive and installation instructions.

NB: If recommended adhesive is not used, claims will not be accepted.

All seams must be sealed.

Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or www.irvineflooring.co.nz
 Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
 Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
 Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.