



Construction	Textured Loop Pile
Yarn	100% Stainproof SDX (Solution Dyed Nylon)
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m ²
Total Weight	4275g/m ²
Pile Height	4.0mm
Total Thickness	8.0mm
Machine Gauge	1/10th
Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (ISO 6356 & EN 1307)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Fire Rating	ISO 9239-1
VOC Rating	Pass (GBCSA/GLP Criteria)
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	Low VOC, solution dyeing uses no water. ISO 14001, Greentag Certified
Installation	Laying recommendation: Quarter turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.