



Construction	Heterogeneous Sheet Vinyl
Width	2.0m & 3.0m
Standard Roll Length	30m
Pattern Repeat	Refer to Vinyl Range Statement
Total Weight	1750g/m ²
Wearlayer Thickness	0.3mm
Total Thickness	2.8mm
Surface Protection	PU / Natural Feel
Slip Resistance	DS-R10 (DIN 51130)
Fire Rating	Bfl-S1 (EN 13501)
Acoustic Insulation	18dB (ISO 717)
Thermal Insulation	0.25W/mK (EN 12524)
Underfloor Heating	Suitable
Chemical Resistance	Very Good (EN ISO26987)
Classification	Class 23 Domestic Heavy
Warranty	10 Year Residential Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.