Network

Belgotex[®]





















Responsible

Underfloor Heating

Castor Chair

500 x 500mm

Construction	Tufted textured loop pile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m ²
Yarn Weight	690g/m²
Total Weight	4600g/ m ² - Vinyl Backings / 4200g/m ² - Cushion Back
Pile Height	3.5mm
Total Thickness	7.0mm
Machine Gauge	1/12th
Primary Backing	Non-woven Polyester / Nylon
Secondary Backing	PVC
Electrical Properties	Antistatic
Electrical Propensity	0.2kV - ISO6356
Fire Rating	ASTM E648-08
VOC Rating	<0.5mg/m²/h - Green Label Plus ASTM D5116-06 // E1 - HCHO
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	23dB (ISO140-8)
Acoustic Absorption	αω 0.15 (EN ISO11654)
Dimensional Stability	<0.20% (EN986)
Thermal Insulation	.04m². kW (IS08302)
Underfloor Heating	Suitable
Colour Fastness	5/5 on Grey Scale (AATCC/16)
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	Low VOC, solution dying uses no water ISO 14001, Green Label Plus Certification
Installation	Laying recommendation: Quarter turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

