Belgotex







BRUNEL























Environmental

Installation

| Construction | Tufted Cut Pile Carpet |
|----------------------|---|
| Yarn | 100% New Zealand Wool |
| Yarn Specification | 2-ply yarn, hank dyed |
| Width | 4.0m |
| Standard Roll Length | 30m |
| Yarn Weight | 1550g/m² / 45.7oz/yd² |
| Total Weight | 2593g/m ² |
| Pile Height | 10.3mm |
| Total Thickness | 13.0mm |
| Machine Gauge | 1/8" |
| Backing | Action Bac |
| Fire Test | ISO 9239-1 |
| Insect Resistance | Treated against insect and moth infestation. |
| Thermal Conductivity | 0.22 m ² / K/W |
| Underfloor Heating | Suitable |
| Luxury Class | LC 5 |
| Rating | Class 23 Domestic Heavy / Class 32 Commercial Medium |
| Warranties | 15 Year Best Wool Warranty Including: Lifetime Manufacturing Defects Warranty 5 Year Insect Resistance Warranty |

GUT Certified, Low VOC, EN 14041

All seams must be sealed.

- For samples, range and warranty details please contact us on 0800 377 753 or www.irvineflooring.co.nz
 Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
 Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
 Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Please contact Gilt Edge Industries for all adhesive and installation instructions.

NB: If recommended adhesive is not used, claims will not be accepted.

Must be laid in accordance with AS/NZ Installation Standards.