## amtico Access

## **Belgotex**<sup>®</sup>























estraint

iciicaliy	Antistatic	Juliable Ful	Castor Ciran	TC II
ısible		Underfloor Heating	Compatible	Slip Res

Construction	Luxury Vinyl Tile		
Plank/Tile Size	Various sizes available.		
Weight	7800g/m²		
Wear Layer Thickness	0.55mm		
Total Thickness	5.0mm		
Surface Protection	Urethane		
Slip Resistance	DS-R10 (DIN 51130 / EN 13893)		
Fire Rating	CRF 9.8kW/m² (ISO 9239-1)		
Impact Sound Reduction	3dB (EN ISO 717-2)		
Residual Indentation	≤0.1mm (ISO 24343-1 / EN 433)		
Abrasion Resistance	Group T, Type 1 (EN ISO 10582 / EN 649)		
Dimensional Stability	≤0.15% (EN 14565 Annex C)		
Underfloor Heating	Suitable		
Curling	≤1mm (EN ISO 23999, EN 434)		
Light Stability	≥6 (ISO 105 B02)		
Resistance to Chemicals	Excellent (EN ISO 26987 / EN 423)		
Classifications	Class 23 Domestic Heavy / Class 33 Commercial Heavy / Class 42 Industrial Medium		
Warranties	20 Year Residential / 10 Year Commercial Warranty		
Environmental	ISO 14001, A/A+ rating (BRE Green Guide) Manufactured using phthalate free and bio based plasticisers except for recycled content. QB UPEC certified (UPEC 326-001.1) BREEAM certified (ENP 468)		
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions.  NB: If recommended adhesive is not used, claims will not be accepted.  Must be laid in accordance with AS/NZ Installation Standards.		

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Verify substrate (concrete) is dry per NZ specifications maximum relative humidity.