Abstract

Belgotex[®]

























| (m) | |
|-------------|--|
| Stain Proof | |

Suitable For Underfloor Heating

| Construction | Patterned Tufted Cut Pile Carpet |
|----------------------------|--|
| Yarn | 100% Premium Solution Dyed Nylon |
| Width | 4.0m |
| Standard Roll Length | 35m |
| Pattern Repeat | ± W 97cm x L 99cm |
| Yarn Weight | 1200g/m² / 36oz/yd² |
| Total Weight | 2500g/m² |
| Pile Height | 7.0mm |
| Total Thickness | 10mm |
| Machine Gauge | 1/10th |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | FusionBac |
| Electrical Properties | Antistatic |
| Electrical Propensity | < 2kV (EN 1307 / ISO 6356) |
| Fire Rating | ISO 9239-1 |
| VOC Rating | Pass (GBCSA/GLP Criteria) |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Underfloor Heating | Suitable - Maximum Temperature 37°C |
| Rating | Extra Heavy Duty Residential / Heavy Duty Commercial |
| Stair Rating | Suitable |
| Warranties | 20 Year Premium Warranty 20 Year Residential Wear Warranty 20 Year Stain Proof Warranty 20 Year Fade Proof Warranty 20 Year Colourfast Warranty 5 Year Manufacturing Defects Warranty 10 Year Commercial Wear Warranty |
| Environmental | Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dying uses no water, Eco-Wash™ Treatment, ISO 14001 |
| Installation | Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. |
| | |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.