

# Alexandria



|                                   |  |
|-----------------------------------|--|
| <b>Construction</b>               | Scroll Loop Pile Carpet  |
| <b>Yarn</b>                       | 100% Solution Dyed Nylon   |
| <b>Width</b>                      | 4.0m   |
| <b>Standard Roll Length</b>       | 35m  |
| <b>Yarn Weight</b>                | 1460g/m <sup>2</sup> / 43oz/yd <sup>2</sup>  |
| <b>Total Weight</b>               | 2365g/m <sup>2</sup>   |
| <b>Pile Height</b>                | 9.0mm  |
| <b>Total Thickness</b>            | 11.0mm   |
| <b>Machine Gauge</b>              | 1/5 ”  |
| <b>Primary Backing</b>            | Woven Polypropylene  |
| <b>Secondary Backing</b>          | Action Fleece  |
| <b>Electrical Properties</b>      | Antistatic   |
| <b>Electrical Propensity</b>      | < 2kV (EN 1815 / ISO 6356)   |
| <b>Fire Rating</b>                | CRF 4.8kW/m <sup>2</sup> (AS/ISO 9239-1)   |
| <b>Anti-allergenic Properties</b> | Will not shed or pill. Resistant to mould & mildew.  |
| <b>Underfloor Heating</b>         | Suitable   |
| <b>Rating</b>                     | Extra Heavy Duty Residential<br>Heavy Duty Commercial  |
| <b>Stair Rating</b>               | Suitable   |
| <b>Warranties</b>                 | 15 Year Residential Warranty<br>5 Year Commercial Warranty   |
| <b>Installation</b>               | Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>All seams must be sealed.<br>Must be laid in accordance with AS/NZ Installation Standards. |
| <b>Environmental</b>              | CRI Green Label Certified<br>Low VOC, solution dyeing uses no water<br>ISO 14001, ISO 9001, ISO 45001  |



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

## A World of Perfect Choices