

Ambiance Ultra



Construction	Homogeneous Sheet Vinyl
Width	2.0m
Standard Roll Length	20m
Pattern Repeat	Random repeat, directional laying
Total Weight	2750g/m ²
Wear Layer Thickness	2.0mm
Total Thickness	2.0mm
Surface Protection	Evercare™
Slip Resistance - Oil-Wet Ramp	R10 (AS4586:2013)
Slip Resistance - Wet Pendulum	P4 (AS4586:2013, App A)
Electrical Propensity	≤ 2kV (EN 1815)
Fire Rating	CRF 10.4kW/m ² (ISO 9239-1)
Type Binder Content	I (EN ISO 10581)
Dimensional Stability	≤0.40% (EN ISO 23999, EN 434)
Thermal Insulation	0.25W/mK (ISO 10456)
Indoor Air Quality	TVOC after 28 days <10µg/m ³ (ISO 16000-6) FloorScore®
Anti-bacterial Activity (E. coli - S. aureus)	> 99% inhibits growth (ISO 22196)
Underfloor Heating	Suitable up to 27°C
Colour Fastness	≥6 (ISO 105 - B02)
Chemical Resistance	OK (EN ISO 26987)
Classification	Class 34 Commercial Very Heavy Class 43 Industrial Heavy
Warranties	12 Year Commercial Warranty
Installation	Cove fillet is required on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified 100% REACH Compliant 100% Recyclable Environmental Product Declaration



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.

Belgotex®

A World of Perfect Choices