

Amiral



Construction	Tufted Saxony Cut Pile Carpet
Yarn	100% Nylon
Width	4.0m
Pattern Repeat	W 2.5cm x L 2.5cm
Yarn Weight	1200g/m ²
Total Weight	2285g/m ²
Pile Height	5.8mm
Total Thickness	8.5mm
Machine Gauge	1/10th
Backing	Action Back
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 9.8kW/m ² (ISO 9239-1)
VOC Rating	A+ (AGBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 30dB (ISO 140-8)
Acoustic Absorption	α _w 0.25 (ISO 11654)
Underfloor Heating	Suitable
Stair Rating	Suitable
Luxury Class	LC4
Rating	Heavy Duty Commercial
Warranties	5 Year Residential Warranty 5 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GUT Label, LEED® CRI Green Label Plus Low VOC, 100% Green Electricity Environmental Management ISO 14001 Quality Management ISO 9001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices