

Amtico Form



Construction	Luxury Vinyl Tile
Plank Size	Various sizes available
Total Weight	Natural Wood - 3277g/m ² Stone - 3472g/m ²
Wear Layer Thickness	0.7mm
Total Thickness	2.5mm
Surface Protection	Urethane
Slip Resistance	DS-R10 (DIN 51130 / EN 13893)
Fire Rating	Natural Wood - CRF 10.3kW/m ² (ISO 9239-1) Stone - CRF 9.9kW/m ² (ISO 9239-1)
Impact Sound Reduction	4dB (EN ISO 717-2)
Residual Indentation	≤ 0.1mm (EN ISO 24343-1, EN 433)
Abrasion Resistance	Group T, Type 1 (EN ISO 10582 / EN 649)
Dimensional Stability	≤0.25% (ISO 23999 / EN 434)
Indoor Air Quality	A+ Emissions
Underfloor Heating	Suitable
Curling	≤2mm (ISO 23999 / EN 434)
Light Stability	≥6 (EN 20 105 - B02)
Chemical Resistance	Excellent (EN ISO 26987 / EN 423)
Classification	Class 23 Domestic Heavy Class 34 Commercial Very Heavy Class 43 Industrial Heavy
Warranties	30 Year Residential Warranty 12 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	A/A+ rating (BRE Green Guide) Manufactured using phthalate free and bio based plasticisers except for recycled content. QB UPEC certified (UPEC 326-001.1) BREEAM certified (ENP 468) Environmental Management ISO 14001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices