

<b>Construction</b>	Luxury Vinyl Tile
<b>Plank Size</b>	Various sizes available
<b>Total Weight</b>	2600g/m <sup>2</sup>
<b>Wear Layer Thickness</b>	0.55mm
<b>Total Thickness</b>	2.0mm
<b>Surface Protection</b>	Urethane
<b>Slip Resistance</b>	DS-R10 (DIN 51130 / EN 13893)
<b>Fire Rating</b>	Natural Wood - CRF 10.3kW/m <sup>2</sup> (ISO 9239-1) Stone - CRF 9.9kW/m <sup>2</sup> (ISO 9239-1)
<b>Impact Sound Reduction</b>	4dB (EN ISO 717-2)
<b>Residual Indentation</b>	≤ 0.1mm (EN ISO 24343-1, EN 433)
<b>Abrasion Resistance</b>	Group T, Type 1 (EN ISO 10582 / EN 649)
<b>Dimensional Stability</b>	≤0.25% (ISO 23999 / EN 434)
<b>Indoor Air Quality</b>	A+ Emissions
<b>Underfloor Heating</b>	Suitable
<b>Curling</b>	≤2mm (ISO 23999 / EN 434)
<b>Light Stability</b>	≥7 (EN 20 105 - B02)
<b>Chemical Resistance</b>	Excellent (EN ISO 26987 / EN 423)
<b>Classification</b>	Class 33 Commercial Very Heavy Class 42 Industrial Medium
<b>Warranties</b>	10 Year Commercial Warranty
<b>Installation</b>	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	A/A+ rating (BRE Green Guide) Manufactured using phthalate free and bio based plasticisers except for recycled content. QB UPEC certified (UPEC 326-001.1) BREEAM certified (ENP 468) Environmental Management ISO 14001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.