

Amtico Signature Acoustic



Construction	Luxury Vinyl Tile
Plank/Tile Size	Various sizes available
Cross Grain Size	457.2 & 914.4mm in length
Total Weight	3330g/m ²
Wear Layer Thickness	1.0mm
Total Thickness	3.5mm
Surface Protection	Urethane
Slip Resistance	DS-R10 (DIN 51130 / EN 13893)
Fire Rating	CRF 10.0kW/m ² (ISO 9239-1)
Impact Sound Reduction	18dB (EN ISO 717-2)
Residual Indentation	≤ 0.1mm (EN ISO 24343-1, EN 433)
Dimensional Stability	≤0.25% (ISO 23999 / EN 434)
Thermal Insulation	0.040m ² K/W (EN 12667)
Indoor Air Quality	A+ Emissions
Underfloor Heating	Suitable
Curling	≤2mm (ISO 23999 / EN 434)
Light Stability	≥7 (EN 20 105 - B02)
Chemical Resistance	Excellent (EN ISO 26987 / EN 423)
Classification	Class 23 Domestic Heavy Class 33 Commercial Heavy Class 4 Industrial Medium
Warranties	Lifetime Residential Warranty Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	A/A+ rating (BRE Green Guide) Manufactured using phthalate free and bio based plasticisers except for recycled content. QB UPEC certified (UPEC 326-001.1) BREEAM certified (ENP 468) Environmental Management ISO 14001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices