

Amtico Spacia Acoustic



Construction	Luxury Vinyl Tile
Plank/Tile Size	184.2mm x 1219.2mm Various sizes available indent
Total Weight	3600g/m ²
Wear Layer Thickness	0.55mm
Total Thickness	3.5mm
Surface Protection	Urethane
Slip Resistance	DS-R10 (DIN 51130 / EN 13893)
Fire Rating	CRF 9.8kW/m ² (ISO 9239-1)
Impact Sound Reduction	18dB (EN ISO 717-2)
Residual Indentation	≤ 0.1mm (EN ISO 24343-1, EN 433)
Dimensional Stability	≤0.25% (ISO 23999 / EN 434)
Thermal Insulation	0.032m ² K/W (EN 12667)
Indoor Air Quality	A+ Emissions
Underfloor Heating	Suitable
Curling	Pass (ISO 23999 / EN 434)
Light Stability	7 or better (ISO 105 B02)
Chemical Resistance	Excellent (EN ISO 26987 / EN 423)
Classification	Class 23 Domestic Heavy Class 33 Commercial Heavy Class 42 Industrial Medium
Warranties	25 Year Residential Warranty 10 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	A/A+ rating (BRE Green Guide) Manufactured using phthalate free and bio based plasticisers except for recycled content. QB UPEC certified (UPEC 326-001.1) BREEAM certified (ENP 468) Environmental Management ISO 14001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex[®]

A world of
perfect choices_