

Authentic XXL



Construction	Classenboard HDF, High-density fibreboard (ML 2.0)
Plank Size	243mm x 2175mm
Tiles per Carton	4pcs / 2.114m ²
Total Weight	1353g/m ²
Wear Layer Thickness	0.1mm
Total Thickness	12.0mm
Locking System	Megaloc®
Surface Protection	Aluminum Oxide
Finish	Embossed in Register
Slip Resistance	DS (EN 13893)
Electrical Propensity	<2kV (EN 1815)
Fire Rating	CRF 6.28kW/m ² (ISO 9239-1)
Residual Indentation	< 0.05 mm (ISO 24343-1)
Surface Soundness	≥1.25N/mm ² (EN 311)
Thermal Insulation	≤0.15W/mK (EN 12667)
Indoor Air Quality	A+ Emissions
Underfloor Heating	Suitable
Wet Areas	Not Suitable
Light Fastness	≥4 (EN 20105-A02)
Formaldehyde Group	E1 (EN 717-1)
Resistance to Staining	5 (group 1 and 2), 4 (group 3) - (EN 438)
Wear Resistance	IP ≥6000 cycles (AC5) - (EN 13329)
Castor Chair Resistance	no damage with type W after 25 000 cycles (EN 425)
Impact Resistance	Small - diameter ball ≥ 15 N / Large - diameter ball ≥ 1000 mm (EN 133329)
Locking Strength	F10.2 ≥1.0kN/mm / FS0.2 ≥2.0kN/mm (ISO 24334)
Thickness Swelling	≤15% (EN 13329)
Abrasion Grade	AC 4
Movement of a Furniture Leg	No damage with type 0 (EN 424)
Classification	Class 33 Commercial Heavy
Warranties	20 Year Residential Warranty 10 Year Commercial Warranty
Installation	Must be properly installed according to the installation instructions.
Environmental	Blue Angel Certified GREENGUARD Gold Certification Environmental Management ISO 14001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.

Belgotex®

A World of Perfect Choices