Bark II

Belgotex[®]























Stain	Resistant	Fade	Resistant

tant

tic

Suitable For

Suitable Fo

Castor Chair

Construction	Tip-Sheared Patterned Loop Pile	
Yarn	100% Solution Dyed Nylon	
Width	3.66m	
Yarn Weight	814g/m²	
Pile Height	3.3mm	
Total Thickness	7.3mm	
Machine Gauge	5/64	
Primary Backing	100% Synthetic	
Secondary Backing	Integra HP	
Electrical Properties	Antistatic	
Electrical Propensity	<3.0kv	
Fire Rating	CRF 5.2kW/m ² (ISO 9239-1)	
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.	
Classification	Heavy Duty Commercial	
Stair Rating	Suitable	
Warranty	15 Year Commercial Warranty Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant	
Environmental	GreenStar, Homestar™, LEED® Well Building Standard® CRI Green Label Plus Certified Environmental Product Declaration Contains Recycled content Low VOC, solution dying uses no water ISO 14001	
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions.	

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.