
Bases Loaded

Belgotex[®]













Construction	Tufted Cut Pile Carpet
Yarn	100% Solution Dyed Polyester
Width	3.66m
Standard Roll Length	40m
Yarn Weight	1010g/m² / 30oz/yd²
Pile Height	7.0mm
Total Thickness	9.0mm
Machine Gauge	1/8th
Primary Backing	Woven Polypropylene
Secondary Backing	Action Fleece
Electrical Properties	Antistatic
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Medium Duty Residential
Stair Rating	Suitable
Warranties	5 Year Living Warranty 5 Year Residential Wear Warranty 5 Year Stain Resistant Warranty 5 Year Fade Resistant Warranty 5 Year Colourfast Warranty 1 Year Manufacturing Defects Warranty
Environmental	Low VOC, solution dying uses no water CRI Green Label Plus, Post consumer recycled content ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

• Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.

Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.