



Stain Resistant



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Anti-Allergenic



Suitable For Stairs



Construction	Tufted Loop Pile Carpet
Yarn	100% New Zealand Wool
Width	4.0m
Standard Roll Length	30m
Yarn Weight	1300g/m ² / 38.4oz/yd ²
Total Weight	2414g/m ²
Pile Height	5.2mm
Total Thickness	8.4mm
Machine Gauge	5/32"
Backing	Action Bac
Fire Test	CFL-s1 (EN 13501)
Insect Resistance	Treated against insect and moth infestation
Thermal Conductivity	0.14 m ² / K/W
Underfloor Heating	Suitable
Luxury Class	LC 4
Rating	Class 23 Domestic Heavy / Class 33 Commercial Heavy
Warranties	7 Year Best Wool Warranty 5 Year Best Wool Stair Warranty
Environmental	GUT Certified, Low VOC, EN 14041
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.