

BJELIN Parquet Herringbone



Category	Engineered Timber
Type	3 Layer Parquet: Herringbone
Plank Size	69mm x 345mm
Planks per Carton	19pcs / 0.452m ²
Weight per Carton	5.5kg
Thickness	14.5mm
Top Layer Thickness	2.5mm
Surface Finishing	Mattlack, gloss 10 OP
Core	Fir or Spruce
Locking System	Välinge 2G / 5G
Slip Resistance	Dry 68 / Wet 24 USRV (CEN/TS 1576:2010, EN 14342:2013)
Thermal Resistance	0.14 m ² K/W (EN 14342:2013)
Fire Rating	Dfl-s1 (EN 14342:2013)
Formaldehyde Group	E1 (EN 14342:2013)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Performance Classification	HRN EN 350-2:2005 (EN 14342:2013)
Stair Rating	Suitable
Warranties	25 Year Residential Warranty Commercial on Request
Installation	Must be properly installed according to the installation instructions. Glue down installation: please contact MBP (NZ) Ltd for Mapei adhesive recommendation and install instructions.
Environmental	Forest Stewardship Council (FSC) Nordic Swan Ecolabel Certified Greengard Gold Quality Management ISO 9001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.

Belgotex®

A World of Perfect Choices