

BJELIN Parquet



Category	Engineered Timber
Type	3 Layer Parquet: 1 - strip
Plank Size	182mm x 2200mm
Planks per Carton	6pcs / 2.40m ²
Weight per Carton	18.41kg
Thickness	14.5mm
Top Layer Thickness	2.5mm
Surface Finishing	Lacquer, gloss 10 OP
Core	Fir or Spruce
Locking System	Välinge 2G / 5G
Slip Resistance	Dry 68 / Wet 24 USRV (CEN/TS 1576:2010, EN 14342:2013)
Thermal Resistance	0.14 m ² K/W (EN 14342:2013)
Fire Rating	Dfl-s1 (EN 14342:2013)
Formaldehyde Group	E1 (EN 14342:2013)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Performance Classification	HRN EN 350-2:2005 (EN 14342:2013)
Stair Rating	Suitable
Warranties	20 Year Residential Warranty Commercial on Request
Installation	Must be properly installed according to the installation instructions.
Environmental	Forest Stewardship Council (FSC) Nordic Swan Ecolabel Certified Greengard Gold Quality Management ISO 9001 Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.

Belgotex®

A World of Perfect Choices