

Category	European Hardened Timber
Type	100% Real Wood - Oak
Plank Size	206mm x 2200mm
Planks per Carton	4pcs / 1.8128m ²
Weight per Carton	11.0kg
Thickness	11.3mm
Top Layer Thickness	0.6mm
Surface Finishing	Pro Matt Lacquer
Core	Ultra HDF
Locking System	Välinge 5G Dry
Slip Resistance	USRV 40 (CE /TS 15676:2008 / EN 14342:2013)
Thermal Resistance	0.07 m ² K/W (EN 12667)
Thickness Swelling	<10% (EN 14354)
Fire Rating	CRF ≥ 8.8 kW/m ² (ISO 9239-1) Bfl-s1 (EN 13501-1)
Indoor Air Quality	A+ Emissions / Indoor Air Comfort Gold®
Formaldehyde Group	E1 (EN 717-1)
Wear Resistance	>6000 cycles (EN 14354)
Impact Resistance	EC3 (EN 14354)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Classification	Class 23 Domestic Heavy Class 33 Commercial Heavy
Stair Rating	Suitable
Warranties	35 Year Residential Warranty 15 Year Moisture Protection (Kitchen, Laundry, Toilet) Commercial on Request
Installation	Must be properly installed according to the installation instructions. Glue down installation: please contact MBP (NZ) Ltd for Mapei adhesive recommendation and install instructions.
Environmental	Forest Stewardship Council (FSC) Nordic Swan Ecolabel Certified Greengard Gold Quality Management ISO 9001 Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.