



BOEN Plank 209 Live Pure



Construction	Engineered Timber
Plank Size	209mm x 2200mm
Planks per Carton	6pcs / 2.76m ²
Weight per Carton	20kg
Thickness	14mm
Top Layer Thickness	2.7mm
Surface Finishing	Live Pure Lacquer
Surface Structure	Brushed
Core	Spruce
Locking System	5G Click
Bevel	2V
Slip Resistance- Ramp Test	R11 (DIN 51130)
Thermal Conductivity	0.129 m2K/W (EN 12667)
Thermal Resistance	0.109 m2K/W (EN 12667)
Fire Rating	CRF ≥ 4.5 kW/m2 (ISO 9239-1)
Indoor Air Quality	FloorScore®
Underfloor Heating	Suitable - Maximum Temperature 27°C
Performance Classification	Class 1 (EN 14342:2013)
Stair Rating	Suitable
Warranties	20 Year Residential Warranty Commercial on Request
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Blue Angel Certified Nordic Swan Ecolabel Certified Environmental Management ISO 14001 Toitu Carbonreduce Organisation Certified



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.

Belgotex®

A World of Perfect Choices