



BOEN Plank 209 Live Pure



Category	Engineered Timber
Plank Size	209mm x 2200mm
Planks per Carton	6pcs / 2.76m ²
Weight per Carton	20kg
Thickness	14mm
Top Layer Thickness	2.7mm
Surface Finishing	Live Pure Lacquer
Surface Structure	Brushed
Core	Spruce
Locking System	5G Click
Bevel	2V
Slip Resistance- Ramp Test	R11 (DIN 51130)
Thermal Conductivity	0.129 m2K/W (EN 12667)
Thermal Resistance	0.109 m2K/W (EN 12667)
Fire Rating	CRF ≥ 4.5 kW/m2 (ISO 9239-1)
Indoor Air Quality	FloorScore®
Underfloor Heating	Suitable - Maximum Temperature 27°C
Performance Classification	Class 1 (EN 14342:2013)
Stair Rating	Suitable
Warranties	20 Year Residential Warranty Commercial on Request
Installation	Must be properly installed according to the installation instructions.
Environmental	Blue Angel Certified Nordic Swan Ecolabel Certified Environmental Management ISO 14001 Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.

Belgotex®

A World of Perfect Choices