



Construction	Engineered Timber
Plank Size	181mm x 2200mm
Planks per Carton	8pcs / 3.19m²
Weight per Carton	23.5kg
Thickness	13.2mm
Top Layer Thickness	2.7mm
Surface Finishing	Live Pure Lacquer
Surface Structure	Brushed
Core	Spruce
Locking System	5G Click
Bevel	2V
Slip Resistance- Ramp Test	R11 (DIN 51130)
Thermal Conductivity	0.127 m2K/W (EN 12667)
Thermal Resistance	0.104 m2K/W (EN 12667)
Fire Rating	CRF ≥ 4.5 kW/m2 (ISO 9239-1)
Indoor Air Quality	FloorScore®
Underfloor Heating	Suitable - Maximum Temperature 27°C
Rating	Extra Heavy Duty Residential Heavy Duty Commercial
Stair Rating	Suitable
Warranties	20 Year Residential Warranty Commercial on Request
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions.  NB: If recommended adhesive is not used, claims will not be accepted.  Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Blue Angel Certified Nordic Swan Ecolabel Certified Environmental Management ISO 14001 Toitu Carbonreduce Organisation Certified









- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.

Belgotex<sup>®</sup>

A World of Perfect Choices