Broadlane

Construction	Tufted Cut Pile Carpet
Yarn	100% Solution Dyed Nylon
Width	3.66m
Standard Roll Length	30m
Yarn Weight	26oz/yd²
Total Weight	2510g/m²
Pile Height	6.0mm
Total Thickness	8.0mm
Machine Gauge	1/10th
Primary Backing	Woven Polypropylene
Secondary Backing	Synthetic Jute
Electrical Properties	Antistatic
Electrical Propensity	< 2kV
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Stair Rating	Suitable
Rating	Heavy Duty Residential
Warranties	10 Year Residential Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Environmental Management ISO 14001 Quality Management ISO 9001

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices