

# Brookvale



|                                   |                                                                                                                                                                                                                                                            |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction</b>               | Tufted Cut Pile Carpet                                                                                                                                                                                                                                     |
| <b>Yarn</b>                       | 100% Solution Dyed Nylon                                                                                                                                                                                                                                   |
| <b>Width</b>                      | 3.66m                                                                                                                                                                                                                                                      |
| <b>Standard Roll Length</b>       | 35m                                                                                                                                                                                                                                                        |
| <b>Yarn Weight</b>                | 880g/m <sup>2</sup> / 26oz/yd <sup>2</sup>                                                                                                                                                                                                                 |
| <b>Total Weight</b>               | 1750g/m <sup>2</sup>                                                                                                                                                                                                                                       |
| <b>Pile Height</b>                | 7.0mm                                                                                                                                                                                                                                                      |
| <b>Total Thickness</b>            | 9.0mm                                                                                                                                                                                                                                                      |
| <b>Machine Gauge</b>              | 1/8th                                                                                                                                                                                                                                                      |
| <b>Primary Backing</b>            | Woven Polypropylene                                                                                                                                                                                                                                        |
| <b>Secondary Backing</b>          | Action Fleece                                                                                                                                                                                                                                              |
| <b>Electrical Properties</b>      | Antistatic                                                                                                                                                                                                                                                 |
| <b>Electrical Propensity</b>      | < 2kV                                                                                                                                                                                                                                                      |
| <b>Fire Rating</b>                | CRF 2.6kW/m <sup>2</sup> (ISO 9239-1)                                                                                                                                                                                                                      |
| <b>Anti-allergenic Properties</b> | Will not shed or pill. Resistant to mould & mildew.                                                                                                                                                                                                        |
| <b>Underfloor Heating</b>         | Suitable                                                                                                                                                                                                                                                   |
| <b>Stair Rating</b>               | Suitable                                                                                                                                                                                                                                                   |
| <b>Rating</b>                     | Extra Heavy Duty Residential<br>Light Duty Commercial                                                                                                                                                                                                      |
| <b>Warranties</b>                 | 10 Year Residential Warranty<br>5 Year Commercial Warranty                                                                                                                                                                                                 |
| <b>Installation</b>               | Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>All seams must be sealed.<br>Must be laid in accordance with AS/NZ Installation Standards. |
| <b>Environmental</b>              | CRI Green Label Certified<br>Low VOC, solution dying uses no water<br>Environmental Management ISO 14001<br>Quality Management ISO 9001<br>Occupational Health and Safety Management ISO 45001                                                             |



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

## A World of Perfect Choices