

# Canopy To Bark - Zoom HD

# Belgotex®



<b>Construction</b>	Structured Loop Pile
<b>Yarn</b>	100% Regenerated Solution Dyed ECONYL Nylon
<b>Size</b>	250mm x 1000mm
<b>Tiles per Carton</b>	12pcs / 3.0m <sup>2</sup>
<b>Yarn Weight</b>	1050g/m <sup>2</sup>
<b>Total Weight</b>	5210g/m <sup>2</sup>
<b>Pile Height</b>	5.0mm
<b>Total Thickness</b>	9.7mm
<b>Machine Gauge</b>	1/10
<b>Primary Backing</b>	Non-Woven PVC Free
<b>Secondary Backing</b>	Bitumen
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	≤ 2kV
<b>Fire Rating</b>	Bfl-S1 (EN 14041:2004/AC:2006)
<b>VOC Rating</b>	A+ (AgBB protocol and GUT label)
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.
<b>Acoustic Insulation</b>	27dB (ISO 140-8)
<b>Acoustic Absorption</b>	α <sub>w</sub> 0.25 (ISO 11654)
<b>Dimensional Stability</b>	≤0.20% (EN 986)
<b>Thermal Insulation</b>	<0.15% <sup>m<sup>2</sup>C</sup> /W
<b>Underfloor Heating</b>	Suitable
<b>Colour Fastness</b>	>7/8 on Grey Scale
<b>Classification</b>	Class 33 Commercial Heavy
<b>Stair Rating</b>	Suitable
<b>Warranty</b>	15 Year Commercial Warranty
<b>Environmental</b>	GreenStar, Homestar™, Well building Standard® Gut Label Certified, LEED® CRI Green Label Certified Environmental Product Declaration Low VOC, Contains recycled content ISO 14001
<b>Installation</b>	Laying recommendation: Herringbone or Ashlar. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# B.