

Construction	Heterogeneous Sheet Vinyl
Width	2.0m & 3.0m
Standard Roll Length	22m
Pattern Repeat	Refer to Vinyl Range Statement
Total Weight	2250g/m ²
Wear Layer Thickness	0.2mm
Total Thickness	3.8mm
Surface Protection	Natural Feel
Slip Resistance	DS-R10 (DIN 51130)
Electrical Properties	Antistatic
Electrical Propensity	<2kV (EN 1815)
Fire Rating	ISO 9239-1
Acoustic Insulation	21dB (ISO 717)
Thermal Insulation	0.25W/mK (EN 12524)
Indoor Air Quality	A+ Emissions
Underfloor Heating	Suitable up to 27°C
Chemical Resistance	Very Good (EN ISO 26987)
Classification	Class 23 Domestic Heavy
Warranties	7 Year Residential Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	REACH Certificate of Compliance Quality Management ISO 9001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.