

<b>Construction</b>	Heterogeneous Sheet Vinyl
<b>Width</b>	2.0m
<b>Standard Roll Length</b>	25m
<b>Pattern Repeat</b>	Refer to Vinyl Range Statement
<b>Total Weight</b>	1750g/m <sup>2</sup>
<b>Wear Layer Thickness</b>	0.50mm
<b>Total Thickness</b>	2.2mm
<b>Backing</b>	Compact Backing
<b>Surface Protection</b>	PU Lacquer
<b>Slip Resistance</b>	DS-R10 (EN 16165 annex B)
<b>Fire Rating</b>	Bfl-s1 (EN 13501)
<b>Acoustic Insulation</b>	13dB (ISO 717-2)
<b>Thermal Conductivity</b>	0.110W/mK (EN 12667)
<b>Indoor Air Quality</b>	A+ Emissions
<b>Dimensional Stability</b>	≤ 0.40% (EN ISO 23999)
<b>Residual Indentation</b>	≤0.20mm (EN ISO 24343-1)
<b>Underfloor Heating</b>	Suitable
<b>Chemical Resistance</b>	Very Good (EN ISO 26987)
<b>Classification</b>	Class 33 Commercial Heavy Class 42 Industrial Medium
<b>Warranties</b>	15 Year Residential Warranty 10 Year Commercial Warranty
<b>Installation</b>	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	REACH Certificate of Compliance Quality Management ISO 9001 (PDF)



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.