Conscious

Construction	Textured Hi Low Loop Pile Carpet
Yarn	100% Stainproof Miracle Fibre
Width	4.0m
Standard Roll Length	35m
Yarn Weight	1100g/m² (32.4oz/yd²)
Total Weight	± 2150g/m²
Pile Height	± 7.0mm
Total Thickness	± 10.0mm
Machine Gauge	5/32”
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
Electrical Properties	Antistatic
Fire Rating	SANS 10177-4
VOC Rating	Pass (ASTM D5116)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Stair Rating	Suitable
Rating	Heavy Duty Residential
Warranties	10 Year Residential Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GreenStar Eco-Wash™ Treatment Low VOC, Solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.