

|                             |   |
|-----------------------------|---|
| <b>Construction</b>         | Heterogeneous Sheet Vinyl   |
| <b>Width</b>                | 2.0m & 4.0m   |
| <b>Standard Roll Length</b> | 30m   |
| <b>Pattern Repeat</b>       | Refer to Vinyl Range Statement  |
| <b>Total Weight</b>         | 1800g/m <sup>2</sup>  |
| <b>Wear Layer Thickness</b> | 0.35mm  |
| <b>Total Thickness</b>      | 2.6mm   |
| <b>Backing</b>              | Diamond Back  |
| <b>Surface Protection</b>   | PU Lacquer / Natural Feel   |
| <b>Slip Resistance</b>      | DS-R11* (DIN 51130)   |
| <b>Fire Rating</b>          | CRF 7.4kW/m <sup>2</sup> (ISO 9239-1)   |
| <b>Acoustic Insulation</b>  | ΔLw 18dB (ISO 717-1)  |
| <b>Thermal Insulation</b>   | 0.25W/mK (ISO 10456)  |
| <b>Indoor Air Quality</b>   | A+ Emissions  |
| <b>Underfloor Heating</b>   | Suitable  |
| <b>Chemical Resistance</b>  | Very Good (EN ISO 26987)  |
| <b>Classification</b>       | Class 23 Domestic Heavy<br>Class 32 Commercial Medium   |
| <b>Warranties</b>           | 15 Year Residential Warranty  |
| <b>Installation</b>         | Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>Must be laid in accordance with AS/NZ Installation Standards. |
| <b>Environmental</b>        | REACH Certificate of Compliance<br>Quality Management ISO 9001 (PDF)  |



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.