

# Decochoc

<b>Description</b>	Decochoc Protection and Covering Panel
<b>Thickness</b>	2.0mm +/- 0.15mm
<b>Width</b>	1300mm
<b>Length</b>	3000mm
<b>Weight</b>	2800g/m <sup>2</sup> +/-200
<b>Density</b>	1.40g/cm <sup>3</sup>
<b>Hardness</b>	75ShD
<b>Stabilization</b>	CaZn
<b>Surface</b>	Textured with Optimixt Embossment
<b>Thermal Conductivity</b>	0.17 W/(m.K) (DIN 52612)
<b>Fire Rating</b>	B-s2,d0 (EN 13501-1)
<b>Chemicals resistance</b>	Anios compliant H2O2 compliant
<b>Decontamination of surface (radionuclide)</b>	Excellent (ISO 8690)
<b>Anti-bacterial activity (2) (S. aureus – S. pyogenes)</b>	> 99% inhibits growth (ISO 22196)
<b>Migration of specific metals</b>	<2 (EN12149-A)
<b>Vinyl Chloride</b>	Non detectable (EN12149-B)
<b>Puncture impact</b>	> 15J (EN ISO 6603-1)
<b>Formaldehyde</b>	Non detectable (EN12149-C)
<b>Impact Resistance Charpy</b>	> 30KJ/m <sup>2</sup> (ISO 179-1)
<b>Chemical Resistance</b>	OK (EN ISO 26987)
<b>Indoor Climate</b>	TVOC after 28 days < 15µg/m <sup>3</sup> (ISO 16000-6) A+ Emissions, Greenguard Gold label
<b>Installation</b>	Please see our website for installation instructions. NB: If the recommended installation is not followed, claims will not be accepted.
<b>Environmental</b>	100% REACH Compliant 100% Recyclable



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

## A World of Perfect Choices