

<b>Category</b>	European Hardened Timber
<b>Plank Size</b>	166mm x 1810mm
<b>Planks per Carton</b>	9pcs / 2.704m <sup>2</sup>
<b>Carton Weight</b>	25.7kg
<b>Thickness</b>	10mm
<b>Top Layer Thickness</b>	0.6mm
<b>Surface Finishing</b>	Super Matt
<b>Bevel</b>	Minibevel 4-sided
<b>Core</b>	HDF
<b>Locking System</b>	Unifit X
<b>Slip Resistance</b>	Dry USRV 62.25 Wet USRV 47.75 (CE / TS 15676:2008 / EN 14342:2013)
<b>Thermal Resistance</b>	0.073 m <sup>2</sup> K/W (EN 12667)
<b>Thermal Conductivity</b>	0.14 W/mK (EN 12667)
<b>Fire Rating</b>	Cfl-s1 (EN13501-1)
<b>Indoor Air Quality</b>	Floorscore A+ Emissions
<b>Formaldehyde Group</b>	E1 (EN 717-1)
<b>Wear Resistance</b>	≥6000 Cycles (EN14354)
<b>Underfloor Heating</b>	Suitable - Maximum Temperature 27°C
<b>Classification</b>	Class 23 Domestic Heavy Class 33 Commercial Heavy
<b>Stair Rating</b>	Suitable
<b>Warranties</b>	35 Year Residential Warranty 15 Year Moisture Protection (Kitchen, Laundry, Toilet) Commercial on Request
<b>Installation</b>	Must be properly installed according to the installation instructions.
<b>Environmental</b>	Forest Stewardship Council (FSC) Environmental Product Declaration LEED Certified Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.