



Construction	Classenboard HDF, High-density fibreboard (ML 2.0)
Locking System	Megaloc®
Finish	Embossed in Register
Plank Size	243mm x 2175mm
Tiles per Carton	4pcs / 2.114m <sup>2</sup>
Total Weight	7569g/m <sup>2</sup>
Total Thickness	8.0mm
Slip Resistance	DS (EN 13893)
Electrical Propensity	≤2kV (EN 1815)
Fire Rating	Cfl - S1 (ISO 9239-1)
Surface Soundness	≥1.25N/mm <sup>2</sup> (EN 311)
Thermal Insulation	≤0.07W/mK (EN 12667)
Underfloor Heating	Suitable
Residual Indentation	≤0.05mm (EN ISO 24343-1)
Light Fastness	≥4 (EN 20105-A02)
Formaldehyde Group	E1 (EN 717-1)
Resistance to Staining	5 (group 1 and 2), 4 (group 3) - (EN 438)
Wear Resistance	IP ≥4000 cycles (AC4) - (EN 13329)
Castor Chair Resistance	no damage with type W after 25 000 cycles (EN 425)
Impact Resistance	Small - diameter ball ≥ 12 N / Large - diameter ball ≥ 750 mm (EN 133329)
Thickness Swelling	≤18% (EN 13329)
Locking Strength	F <sub>10.2</sub> ≥1.0kN/mm / F <sub>50.2</sub> ≥2.0kN/mm (ISO 24334)
Movement of a Furniture Leg	No damage with type O (EN 424)
Abrasion Grade	AC 4
Classification	Class 32 Commercial Medium
Stair Rating	Suitable
Warranty	20 Year Residential Warranty / 10 Year Commercial Warranty
Environmental	Blue Angel Certified A+ Emissions EN 14041
Installation	Please contact Gilt Edge Industries for all trim, underlay and installation recommendations. NB: If appropriate trims or underlays are not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.