



Construction	Tufted Multi Hi Low Loop Pile
Yarn	100% Stainproof SDX (Solution Dyed Nylon)
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m ²
Total Weight	± 3450 g/m ²
Pile Height	2.0 - 3.5mm
Total Thickness	± 4.5mm
Machine Gauge	1/10th
Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (EN 1307)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	18dB (EN/ISO 10143-3)
Acoustic Absorption	αω 0.15 (EN/ISO 354:2003)
Underfloor Heating	Suitable
Fire Rating	CRF 8.3kW/m ² (ISO 9239-1)
Fraying Behaviour	Pass (EN 1307)
Dimensional Stability	≤ 0.2% (EN 1307)
Dimensions (Deviations)	0.10% (EN 1307)
VOC Rating	Pass (GBCSA/GBCA)
Colour Fastness	Light 8 (ISO 105 - B02) Rubbing Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12) Water 4 - 5 (ISO 105 - E01)
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dyeing uses no water, ISO 14001
Installation	Laying recommendation: Quarter turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.