Equinox

Construction	Textured Loop Pile
Yarn	100% Stainproof SDX (Solution dyed nylon)
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m²
Pile Weight	640g/m²
Total Weight	4265g/m²
Pile Height	4.5mm
Total Thickness	7.5mm
Machine Gauge	1/10th
Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV (ISO 6356 & EN 1307)
Fire Rating	CRF 7.8kW/m² (ISO 9239-1)
VOC Rating	Pass (GBCSA/GLP Criteria)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Commercial Warranty
Installation	Laying recommendation: Quarter Turn Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified GreenStar, Homestar™ WELL Building Standard® CRI Green Label Certified Low VOC, Solution dying uses no water Product Health Declaration™ Quality Management ISO 9001 Environmental Management ISO 14001 Occupational Health and Safety Management ISO 45001 Science Based Targets Institute

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices