

Exposed



Construction	Patterned Tufted Cut Pile Carpet
Yarn	100% Premium Solution Dyed Nylon
Width	4.0m
Standard Roll Length	35m
Pattern Repeat	± W 197cm x L 139.5cm
Yarn Weight	1200g/m ² / 36oz/yd ²
Total Weight	2680g/m ²
Pile Height	7.0.0mm
Total Thickness	9.5mm
Machine Gauge	1/10th
Primary Backing	Woven Polypropylene
Secondary Backing	MiracleBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (EN 1307 / ISO 6356)
Fire Rating	CRF 2.5kW/m ² (ISO 9239-1)
VOC Rating	Pass (GBCSA/GLP Criteria)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable - Maximum Temperature 37°C
Stair Rating	Suitable
Rating	Extra Heavy Duty Residential Heavy Duty Commercial
Warranties	20 Year Residential Warranty 10 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified GreenStar, Homestar™ WELL Building Standard® Product Health Declaration™ Eco-Wash™ Treatment Low VOC, Solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices