

Construction	Luxury Vinyl Tile
Plank Size	177.8 x 1219.2mm
Tiles per Carton	20pcs / 4.335m ²
Total Weight	3550g/m ²
Wear Layer Thickness	0.3mm
Total Thickness	2.0mm
Surface Protection	High Performance PU
Finish	Embossed
Bevel	4-sided micro-bevel
Slip Resistance	R10 (DIN 51130)
Electrical Propensity	0.1 kV (EN 1815)
Fire Rating	CRF 11.0kW/m ² (ISO 9239-1)
Acoustic Insulation	3dB (EN ISO 717-2)
Residual Indentation	< 0.1 mm (ISO 24343-1)
Dimensional Stability	≤0.25% (ISO 23999)
Thermal Conductivity	0.074 (W/m*K) (EN 12664)
Thermal Resistance	0.027 (m ² *K/W) (ISO 12664)
Indoor Air Quality	FloorScore® A+ Emissions Eurofins Gold Certified
Underfloor Heating	Suitable, max 27°C
Light Stability	Grade 6 (ISO 105-B02:2014)
Classification	Class 23 Domestic Heavy Class 33 Commercial Heavy Class 42 Industrial Medium
Warranties	20 Year Residential Warranty 10 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified, Declare Environmental Product Declaration GREENGUARD Gold Certification ISO 9001, ISO 45001, ISO 14001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.