Farenheit









Construction	Tufted Textured Loop Pile
Yarn	100% Solution Dyed Nylon
	·
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m²
Pile Weight	576g/m²
Total Weight	4550g/m ²
Pile Height	2.8mm
Total Thickness	5.8mm
Machine Gauge	1/10th
Primary Backing	Non-woven Polyester / Nylon
Secondary Backing	PVC
Electrical Properties	Antistatic
Electrical Propensity	0.2kV (ISo 6356)
Fire Rating	CRF 4.5kW/m² (ASTM E 648)
VOC Rating	<0.5mg/m²/h – Green Label Plus (ASTM D5116-06)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 23dB (ISO 140-8)
Acoustic Absorption	αω 0.15 (ISO 11654)
Dimensional Stability	<0.20% (EN 986)
Thermal Insulation	0.04m²k/W (ISO 8302)
Castor Chair Resistance	R ≥2.4 (DIN 54324)
Underfloor Heating	Suitable
Colour Fastness	5/5 on Grey Scale (AATCC/16)
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Commercial Warranty
Installation	Laying recommendation: Quarter Turn or Brick. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	CRI Green Label Certified Low VOC, Solution dying uses no water Quality Management ISO 9001 Environmental Management ISO 14001 Occupational Health and Safety Management ISO 45001





- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.



A World of Perfect Choices