Fan Fold

Construction	Textured Patterned Loop Pile
Yarn	100% Solution Dyed Nylon
Width	3.66m
Pattern Repeat	W 47.6cm x L 65.4cm
Yarn Weight	814g/m² (24oz/yd²)
Pile Height	3.6mm
Total Thickness	7.6mm
Machine Gauge	5/64
Primary Backing	100% Synthetic
Secondary Backing	Integra® HP
Electrical Properties	Antistatic
Electrical Propensity	≤ 3kV
Fire Rating	CRF 5.2kW/m² (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Stair Rating	Suitable
Rating	Heavy Duty Commercial
Warranties	15 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GreenStar, Homestar™, LEED® WELL Building Standard® CRI Green Label Plus Certified Contains recycled content Low VOC, Solution dying uses no water Environmental Product Declaration Environmental Management ISO 14001 Quality Management ISO 9001

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices