## Fast Forward

## **Belgotex**<sup>®</sup>























Stain Resistan

Fade Resist

ant

Environmentally

Antistatic

Suitable For Underfloor Heating

Suitable

table For

Anti-Allergeni

Castor Chair

Chair 500 x 500mm

Easy Fit

Construction	Tufted textured loop pile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m <sup>2</sup>
Yarn Weight	520g/m <sup>2</sup>
Total Weight	4430g/ m²
Pile Height	5.5mm
Total Thickness	8.0mm
Machine Gauge	1/10th
Primary Backing	Non-woven Polyester / Nylon
Secondary Backing	PVC
Electrical Properties	Antistatic
Electrical Propensity	0.2kV (ISO 6356)
Fire Rating	CRF 8.8kW/m² (ISO 9239-1)
VOC Rating	<0.5mg/m²/h – Green Label Plus ASTM D5116-06
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	23dB (ISO 140-8)
Acoustic Absorption	αω 0.15 (EN ISO 11654)
Dimensional Stability	<0.20% (EN 986)
Castor Chair Resistance	R ≥2.4 (DIN 54324)
Thermal Insulation	0.04m²k/W (ISO 8302)
Underfloor Heating	Suitable
Colour Fastness	5/5 on Grey Scale (AATCC/16)
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	7 Year Commercial Warranty
Environmental	Low VOC, solution dying uses no water ISO 14001, Green Label Plus Certification
Installation	Laying recommendation: Quarter turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Must be laid in accordance with AS/NZ Installation Standards.

