

Construction	Heterogeneous Sheet Vinyl
Width	2.0m & 4.0m
Standard Roll Length	±30m
Total Weight	1750g/m ²
Wear Layer Thickness	0.25mm
Total Thickness	2.7mm
Surface Protection	PU Lacquer
Slip Resistance	R10 (DIN 51 130)
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV (EN 1815)
Fire Rating	CRF 8.1kW/m ² (ISO 9239-1)
Acoustic Insulation	ΔLw 18dB (ISO 717/2)
Wear Group	T (EN 660-2)
Curling	≤8mm (EN ISO 23999)
Dimensional Stability	≤0.40% (EN 434)
Thermal Insulation	0.11W/m/K (EN 12524)
Indoor Air Quality	FloorScore®
Underfloor Heating	Suitable
Residual Indentation	≤0.35mm (EN ISO 24343-1, EN 433)
Colour Fastness	≥6 (EN 20 105 - B02)
Chemical Resistance	OK (ISO 26987, EN 423)
Classification	Class 23 Domestic Heavy Class 31 Commercial Light
Warranties	7 Year Residential Warranty
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	100% Recyclable 100% Phthalate Free



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.