Finfloor Evolve

Category	Laminate
Plank Size	194mm x 1331mm
Planks per Carton	8pcs / 2.066m² Future stock 9pcs / 2.3239m² *Call sales hub to confirm
Weight per Carton	16.1kg
Thickness	8mm
Surface Finishing	Wood Impression
Core	Durable low-swell HDF
Bevel	Micro 4V
Locking System	Angle/Angle
Slip Resistance - Dry Floor Friction	DS (EN 14041 / EN 13893)
Slip Resistance - Wet Pendulum	P3 (AS 4586-2013 Appendix A)
Thermal Resistance	Plank only: 0.060 m²K/W (EN 12667) With Aqua Performance underlay: 0.128 m²K/W With Aqua Elite underlay: 0.133 m²K/W
Fire Rating	Bfl-s1, CRF ≥ 8.0 kW/m² (EN 13501-1, EN ISO 9239-1)
Indoor Air Quality	A+ Emissions
Abrasion Resistance	AC6 (EN 13329)
Castor Chair Resistance	No damage with Type W (EN 425)
Impact resistance	IC 3 (EN 13329)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Classification	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranties	**35 Year Residential Warranty** **15 Year Moisture Protection** **10 Year Pet Damage Warranty** **Commercial on Request**
Installation	Must be properly installed according to the installation instructions.
Environmental	EU Ecolabel Cradle to Cradle Certified Environmental Product Declaration LEED® BREEAM Environmental Management ISO 14001

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.

Belgotex®

A World of Perfect Choices