Finfloor Supreme

Category	Laminate
Plank Size	240mm x 1310mm
Planks per Carton	6pcs / 1.8864m²
Weight per Carton	14.0kg
Thickness	8mm
Surface Finishing	Wood Impression (Registered Embossed)
Core	Durable low-swell HDF
Bevel	Micro 4V
Locking System	Angle/Angle
Slip Resistance - Dry Floor Friction	DS (EN 14041 / EN 13893)
Slip Resistance - Wet Pendulum	P2 (AS 4586-2013 Appendix A)
Thermal Resistance	Plank only: 0.060 m²K/W (EN 12667) With Aqua Performance underlay: 0.128 m²K/W With Aqua Elite underlay: 0.133 m²K/W
Fire Rating	CRF 9.0kW/m² (ISO 9239-1)
Indoor Air Quality	A+ Emissions
Abrasion Resistance	AC6 (EN 13329)
Castor Chair Resistance	No damage with Type W (EN 425)
Impact resistance	IC 3 (EN 13329)
Underfloor Heating	Suitable - Maximum Temperature 27°C
Classification	Class 33 Commercial Heavy
Stair Rating	Suitable
Warranties	35 Year Residential Warranty 15 Year Moisture Protection 10 Year Pet Damage Warranty Commercial on Request
Installation	Must be properly installed according to the installation instructions.
Environmental	EU Ecolabel Cradle to Cradle Certified Environmental Product Declaration LEED® BREEAM Environmental Management ISO 14001

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.

Belgotex®

A World of Perfect Choices