



<b>Construction</b>	Textured Patterned Loop Pile
<b>Yarn</b>	100% Regenerated Solution Dyed ECONYL Nylon
<b>Size</b>	457.2mm x 914.4mm
<b>Tiles per Carton</b>	16pcs / 6.7m <sup>2</sup>
<b>Yarn Weight</b>	610.3g/m <sup>2</sup>
<b>Pile Height</b>	2.6mm
<b>Total Thickness</b>	4.3mm
<b>Machine Gauge</b>	5/64
<b>Primary Backing</b>	100% Synthetic
<b>Secondary Backing</b>	Infinity Modular
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	<3.0kv
<b>Fire Rating</b>	CRF 4.9 kW/m <sup>2</sup> (ISO 9239-1)
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.
<b>Classification</b>	Heavy Duty Commercial
<b>Stair Rating</b>	Suitable
<b>Warranty</b>	<b>15 Year Commercial Warranty</b> Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant
<b>Environmental</b>	GreenStar, Homestar™, LEED® Well Building Standard® CRI Green Label Plus Certified Environmental Product Declaration Contains Recycled content Low VOC, solution dyeing uses no water ISO 14001
<b>Installation</b>	Laying recommendation: Horizontal Brick Ashlar. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.