

Granite



Construction	Patterned Tufted Loop Pile	
Yarn	100% Stainproof SDX (Solution dyed nylon)	
Size	500mm x 500mm	
Tiles per Carton	20pcs / 5.0m ²	
Pile Weight	450g/m ²	
Total Weight	3820g/m ²	
Pile Height	2.0mm	
Total Thickness	8.0mm	
Machine Gauge	1/10th	
Backing	EcoBac	
Electrical Properties	Antistatic	
Electrical Propensity	≤ 2kV (ISO 6356 & EN 1307)	
Fire Rating	CRF 8.3kW/m ² (ISO 9239-1)	
VOC Rating	Pass (GBCSA/GLP Criteria)	
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.	
Acoustic Insulation	ΔLw 28dB (EN/ISO 10143-3)	
Acoustic Absorption	α _w 0.30 (EN/ISO 354:2003)	
Colour Fastness	Light	7 (ISO 105 - B02)
	Rubbing	Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12)
	Water	4 - 5 (ISO 105 - E01)
Light Reflective Value (LRV)	Lead	2.46
	Smoke	5.29
	Dolphin	5.42
	Morning Fog	13.27
Underfloor Heating	Suitable	
Rating	Heavy Duty Commercial	
Stair Rating	Suitable	
Warranties	15 Year Commercial Warranty	
Installation	Laying recommendation: Monolithic Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.	
Environmental	GreenStar, Low VOC Solution dyeing uses no water Quality Management ISO 9001 Environmental Management ISO 14001 Occupational Health and Safety Management ISO 45001	



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices