## Grid









Construction	Patterned Tufted Loop Pile				
Yarn	100% Stainproof SDX (Solution dyed nylon)				
Size	500mm x 500mm				
Tiles per Carton	20pcs / 5.0m <sup>2</sup>				
Pile Weight	450g/m²				
Total Weight	3600g/m²				
Pile Height	2.0mm	2.0mm			
Total Thickness	6.0mm				
Machine Gauge	1/10th				
Backing	Bitumen				
<b>Electrical Properties</b>	Antistatic				
Electrical Propensity	≤ 2kV (ISO 6356 & EN 1307)				
Fire Rating	CRF 8.3kW/m² (ISO 9239-1)				
VOC Rating	Pass (GBCSA/GLP Criteria)				
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.				
Acoustic Insulation	ΔLw 28dB (EN/ISO 10143-3)				
Acoustic Absorption	αω 0.30 (EN/ISO 354:2003)				
Colour Fastness	Light Rubbing Wet Dry Water	Rubbing Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12)			
Light Reflective Value (LRV)	Midnight Thunder Sunset	19.2 4.42 4.91	Horizon Sunrise Cloud Break	5.17 5.66 9.31	
Underfloor Heating	Suitable				
Rating	Heavy Duty Commercial				
Stair Rating	Suitable				
Warranties	15 Year Commercial Warranty				
Installation	Laying recommendation: Quarter Turn Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.				
Environmental	Greentag Certified, GreenStar, Homestar™ WELL Building Standard®, CRI Green Label Certified Low VOC, Solution dying uses no water Product Health Declaration™ Quality Management ISO 9001 Environmental Management ISO 14001				







Occupational Health and Safety Management ISO 45001









- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.



A World of Perfect Choices